according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)

Sika[®]

Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Concrete Primer (Quick Cure Primer) (A)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Sika® Concrete Primer (Quick Cure Primer) (A)

Print Date 13.06.2017

Revision Date 13.06.2017

Version 11.1

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

Precautionary statements : **Prevention**:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

P284 In case of inadequate ventilation wear res-

piratory protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel un-

well.

P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

202-966-0
4,4'-methylenediphenyl diisocyanate
227-534-9
diphenylmethane-2,4'-diisocyanate

• 9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

• 219-799-4 2,2'-methylenediphenyl diisocyanate

Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)

Sika®

Revision Date 13.06.2017

Print Date 13.06.2017

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chamical rama	Cloosification	Concortration
Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
4,4'-methylenediphenyl diisocyanate	Acute Tox.4; H332	>= 5 - < 10
101-68-8	Eye Irrit.2; H319	
202-966-0	STOT SE3; H335	
01-2119457014-47-XXXX	Skin Irrit.2; H315	
	Resp. Sens.1; H334	
	Skin Sens.1; H317	
	Carc.2; H351	
	STOT RE2; H373	
	0101 KL2, 11070	
diphenylmethane-2,4'-diisocyanate	Acute Tox.4; H332	>= 5 - < 10
		/= 5 - < 10
5873-54-1	Eye Irrit.2; H319	
227-534-9	STOT SE3; H335	
01-2119480143-45-XXXX	Skin Irrit.2; H315	
	Resp. Sens.1; H334	
	Skin Sens.1; H317	
	Carc.2; H351	
	STOT RE2; H373	
propyl acetate	Flam. Liq.2; H225	>= 5 - < 10
109-60-4	Eye Irrit.2; H319	
203-686-1	STOT SE3; H336	
01-2119484620-39-XXXX	,	
Diphenylmethanediisocyanate, isomeres and homo-	Acute Tox.4; H332	>= 1 - < 2,5
logues	Skin Irrit.2; H315	,,
9016-87-9	Eye Irrit.2; H319	
3010-07-3	Resp. Sens.1; H334	
	Skin Sens.1; H317	
	Carc.2; H351	
	STOT SE3; H335	
	STOT RE2; H373	
O Ol manthada and dia basad diiba a a a a fa	A suits Tax A 11000	> 0.4 : 4
2,2'-methylenediphenyl diisocyanate	Acute Tox.4; H332	>= 0,1 - < 1
2536-05-2	Eye Irrit.2; H319	
219-799-4	STOT SE3; H335	
01-2119927323-43-XXXX	Skin Irrit.2; H315	
	Resp. Sens.1; H334	
	Skin Sens.1; H317	
	Carc.2; H351	
	STOT RE2; H373	
Substances with a workplace exposure limit :		
2-methoxy-1-methylethyl acetate	Flam. Liq.3; H226	>= 25 - < 40
ountry GR 000000604217	• •	3 / 1

Version 11.1

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

1400.05.0]	ı	
108-65-6			
203-603-9			
01-2119475791-29-XXXX			
Contains:			
2-methoxypropyl acetate <= 1 %			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)

Revision Date 13.06.2017

Version 11.1

Print Date 13.06.2017

May cause respiratory irritation. Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1

Methods for cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid formation of aerosol. Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
		STEL	100 ppm 548 mg/m3	GB EH40
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40
diphenylmethane-2,4'-diisocyanate	5873-54-1	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40
propyl acetate	109-60-4	TWA	200 ppm 849 mg/m3	GB EH40
		STEL	250 ppm 1.060 mg/m3	GB EH40
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	urinary diamine: 1µmol/mol creati- nine (Urine)	Post task	GB EH40 BAT
diphenylmethane-2,4'- diisocyanate	5873-54-1	urinary diamine: 1µmol/mol creati- nine (Urine)	Post task	GB EH40 BAT
Diphenylmethanediisocy- anate, isomeres and homologues	9016-87-9	urinary diamine: 1µmol/mol creati- nine (Urine)	Post task	GB EH40 BAT
2,2'-methylenediphenyl diisocyanate	2536-05-2	urinary diamine: 1µmol/mol creati- nine (Urine)	Post task	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : characteristic

Odour Threshold : No data available

Flash point : 40 °C

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)

Revision Date 13.06.2017 Print Date 13.06.2017 Version 11.1

: 333 °C Autoignition temperature

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : 1,5 %(V)

Upper explosion limit (Vol-%) : 10,8 %(V)

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

: No data available рΗ

Melting point/range / Freez-

ing point

Boiling point/boiling range

: No data available

: No data available

: No data available

Vapour pressure : 3,1 hPa

Density : ca.1,1 g/cm3

at 20 °Č

: insoluble Water solubility

Partition coefficient: n-

octanol/water

: No data available Viscosity, dynamic

Viscosity, kinematic : > 7 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Test atmosphere: dust/mist Method: Expert judgement

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)

Revision Date 13.06.2017

Version 11.1

Print Date 13.06.2017

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

: This substance/mixture contains no components considered Assessment

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

mation

Additional ecological infor- : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1263

14.2 Description of the goods : PAINT RELATED MATERIAL

14.3 Class: 314.4 Packing group: IIIClassification Code: F1Labels: 3Tunnel restriction code: (D/E)14.5 Environmentally hazard-: no

ous ADR

Transport according to chapter 3.4 (LQ) possible

IATA

14.1 UN number : 1263

14.2 Description of the goods : Paint related material

 14.3 Class
 : 3

 14.4 Packing group
 : III

 Labels
 : 3

 14.5 Environmentally hazard : no

ous

IMDG

14.1 UN number : 1263

14.2 Description of the goods : PAINT RELATED MATERIAL

 14.3 Class
 : 3

 14.4 Packing group
 : III

 Labels
 : 3

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



 Revision Date 13.06.2017
 Version 11.1
 Print Date 13.06.2017

EmS Number 1 : F-E EmS Number 2 : S-E 14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

(4,4'-methylenediphenyl diisocya-

nate)

(diphenylmethane-2,4'-diisocyanate) (Diphenylmethanediisocyanate, isomeres and homologues) (2,2'-methylenediphenyl diisocya-

nate)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-

jor-accident hazards involving dangerous substances.

Quantity 1

Quantity 2

P5c FLAMMABLE LIQUIDS

5.000 t

50.000 t

VOC-CH (VOCV) : 33,86 %

VOC-EU (solvent) : 33,86 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- : Environmental Protection Act 1990 & Subsidiary Regulations

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

mental regulation/legislation specific for the substance or mixture:

Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Resp. Sens.	Respiratory sensitisation

Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

according to Regulation (EC) No. 1907/2006

Sika® Concrete Primer (Quick Cure Primer) (A)



Revision Date 13.06.2017 Version 11.1 Print Date 13.06.2017

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!