

Sika[®] Cleaner-S (II)

Contamination remover

Technical Product Data

Chemical base	Water based micro adhesive
Colour	White/grey
Density (CQP ¹ 006-3 / ISO 2811-1)	1.05 kg/l approx.
Flash point (CQP 007-1 / ISO 13736)	103°C
Application temperature	5°C to 45°C
Application method	Lint free paper towel
Storage	Store in sealed container in a cool dry place below 25°C
Shelf life	6 months

¹⁾ CQP = Corporate Quality Procedure

Description

Sika[®] Cleaner S (II) is a water based micro abrasive pre-treatment agent which is designed for the removal of contamination from heavily soiled surfaces that cannot be cleaned sufficiently with standard cleaners without scratching the surface.

Sika[®] Cleaner-S (II) is manufactured in accordance with ISO9001/14001 quality assurance system and the responsible care program.

Areas of Application

Sika[®] Cleaner S (II) is designed for the removal of contamination from heavily soiled surfaces.

Method of Application

1. Open the bottle
2. Apply a small amount of Sika[®] Cleaner S (II) onto the surface to be treated.
3. Start scrubbing the soiled area of the substrate. Apply more material if required.
4. Remove remaining Sika[®] Cleaner S (II) from the surface with a clean lint free paper tissue.
5. Use a glass cleaner like Sika[®]-CleanGlass to completely clean the surface prior to other pre-treatment steps. Surfaces must be allowed to dry completely before the next step in surface preparation (e.g. application of Sika Aktivator Pro).

Immediately after use, reseal container tightly. This product is to be used by professional experienced fitters only. If this product is used for other applications other than Automotive Glass Replacement, trials must be carried out prior to use.



Important Note

Compatibility with the current substrate is to be verified prior to the application. Before applying Sika® Cleaner S (II) to sensitive surfaces (e.g. plastics, etc.) it is recommended to test Sika® Cleaner S (II) on a small, possibly non-visible area of the base material.

Before application of adhesive, the surface has to be cleaned and prepared according to Sika's surface preparation recommendations.

Further Information

Copies of the following publications are available on request:

- Material Safety Data Sheets
- Sika Surface Treatment Chart

Packaging Information

Can	250 ml
-----	--------

Value Bases

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Health and Safety Information

For information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Further information available at:

www.sika.co.uk
www.sika.com

Sika Ltd.
Watchmead
Welwyn Garden City
AL7 1BQ
United Kingdom
Tel. +44 (0)1707 394444
Fax +44 (0)1707 329129

