

PRODUCT DATA SHEET

SikaRoof® Aluminium Edge Trim UK

ALUMINIUM EDGING & CORNER TRIM

PRODUCT DESCRIPTION

SikaRoof® Aluminium Edge Trim UK is required for use on exposed roof system edges to restrain the leading edge of a green roof build up.

They can be cut to length, and matching corner pieces are available fo ease of installation.

USES

- As a separator between the substrate and gravel margin where required
- As water-permeable upstand at the eaves edge of monopitched roofs up to max. 5° roof pitch
- Not suitable for use as a structurally effective gravel retainer for pitches of > 5°

CHARACTERISTICS / ADVANTAGES

Permeable to water with 6 mm Ø holes in the vertical leg

PRODUCT INFORMATION

Chemical Base	Aluminium	
Packaging	Pallet/Package depending on quantity	
Appearance / Colour	Mid sheen natural (unpainted)	
Shelf Life	3 Years	
Storage Conditions	Products should be stored and protected from extremes of temperature.	
Dimensions	Available sizes (HxWxL) • 80 x 140 x 2000mm • 100 x 120 x 2000mm • 120 x 140 x 2000mm • 150 x 129 x 2000mm	
Weight	80mm 100mm 120mm 150mm	800g/m 850g/m 900g/m 950g/m

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regu-

Product Data Sheet

SikaRoof® Aluminium Edge Trim UK February 2025, Version 02.01 020945051350000024 lation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

Installation works should be carried out by suitably trained contractors in strict accordance with the project specification.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet SikaRoof® Aluminium Edge Trim UK February 2025, Version 02.01 020945051350000024



