According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sikafloor®-22 PurCem® Part C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ : +44 (0)1707 394444

Telephone +44 (0)1707 329129 Telefax E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Danger

Hazard statements H315 Causes skin irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Revision Date: 04.01.2024	Version 5.3		Print Date 29.02.2024	
	H318 H335	Causes serious eye damage.  May cause respiratory irritation.		
Precautionary statements :	P101	If medical advice is needed, hat container or label at hand.	ve product	
	P102	Keep out of reach of children.		
	Prevention:			
	P271	Use only outdoors or in a well-vea.	ventilated ar-	
	P280	Wear protective gloves/ eye proprotection.	otection/ face	
	Response:			
	P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.			
	Disposal:			
	P501	Dispose of contents/container in	n accordance	

#### Hazardous components which must be listed on the label:

Cement (chromium reduced)

#### 2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006.

with local regulation.

The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)			
	Registration number					
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 25 - < 40			
	266-043-4	Eye Dam. 1; H318				
		STOT SE 3; H335				
		(Respiratory system)				
calcium dihydroxide	1305-62-0	Skin Irrit. 2; H315	>= 1 - < 2,5			
	215-137-3	Eye Dam. 1; H318				
	01-2119475151-45-	STOT SE 3; H335				
	XXXX	(Respiratory system)				
Substances with a workplace exposure limit :						
Quartz (SiO2)	14808-60-7		>= 60 - < 80			
, ,	238-878-4					
Quartz (SiO2)	14808-60-7		>= 5 - < 10			
	238-878-4					

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** Cough

Respiratory disorder Excessive lachrymation

Erythema **Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.

irritant effects Risks

Causes skin irritation.

Causes serious eve damage. May cause respiratory irritation.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

#### 5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

## 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

#### 7.3 Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Cement (chromium reduced)	65997-15-1	TWA (inhalable dust)	10 mg/m3	GB EH40		
		TWA (Respirable dust)	4 mg/m3	GB EH40		
calcium dihydroxide	1305-62-0	TWA (Respirable fraction)	1 mg/m3	2017/164/EU		
	Further inforn	Further information: Indicative				
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU		
		TWA	5 mg/m3	GB EH40		
		TWA (Respirable fraction)	1 mg/m3	GB EH40		
		STEL (Respirable fraction)	4 mg/m3	GB EH40		

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

## **Environmental exposure controls**

General advice : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state solid Appearance powder Colour white

Odour odourless

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

Flash point Not applicable

Auto-ignition temperature No data available

Decomposition temperature : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

pH : > 11 (20 °C)

Concentration: 50 %

**Viscosity** 

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : No data available

Density : No data available

Bulk density : ca. 1.480 kg/m3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

#### 10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

Not classified based on available information.

## **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Revision Date: 04.01.2024

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## 12.7 Other adverse effects

## **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue 16 03 03\* inorganic wastes containing dangerous substances

Contaminated packaging 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.2 UN proper shipping name

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.3 Transport hazard class(es)

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good Not regulated as a dangerous good IATA (Cargo) IATA (Passenger) Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Not applicable

Control of Major Accident Hazards Regulations

2015 (COMAH)

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

no VOC duties

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

## Other regulations:

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

#### Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# Sikafloor®-22 PurCem® Part C

Date of last issue: 12.05.2023 Version 5.3 Print Date 29.02.2024

Revision Date: 04.01.2024

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

## **Further information**

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
STOT SE 3 H335 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN