

PRODUCT DATA SHEET

Sika® Stain Block

Prevents existing stains appearing through subsequent coatings.

PRODUCT DESCRIPTION

Sika® Stain Block is a spray applied heavily pigmented white paint which permanently prevents existing stains such as water marks, mould stains, rust, nicotine, grease, soot and pen marks showing through on subsequent coatings.

USES

Ideal for areas that have been affected by damp, mould, nicotine and grease.

PRODUCT INFORMATION

Packaging	400 mL Aerosol
Colour	White
Shelf Life	12 months unopened and stored in the correct conditions
Storage Conditions	Store in cool, dry conditions and protect from sunlight at temperatures between +10 and +25 °C. Keep away from sources of ignition.
Density	1.28-1.36 g/cm ³

CHARACTERISTICS / ADVANTAGES

- Easy application aerosol formula.
- Works on most types household/commercial surfaces.
- Heavily pigmented formula for quick easy coverage.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Use only as directed.
- Do not use on bitumen.
- Always test a small inconspicuous area prior to full application.
- It is users responsibility to determine suitability for use. If in doubt please contact technical services for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS**SUBSTRATE PREPARATION**

If stain is due to water leak or penetrating damp, ensure the source of the stain is cured prior to application. Where patches of mould have grown, wash

areas first with Sika® 404 Fungicidal Wash and allow to dry. Remove rust and soot with a wire brush, wash down areas and allow to dry.

APPLICATION METHOD / TOOLS

Shake the can until a rattling noise is heard then shake for a further 1-2 minutes to mix the paint. Spray Sika® Stain Block onto the affected area from a distance of 20-30 cm until stain is completely covered. Allow to dry for 15 minutes before covering. If the area is to be overcoated with a solvent based paint, first apply a water based primer to ensure compatibility with Sika® Stain Block.

After every application, do not allow paint to dry in the nozzle by turning it upside down and press the nozzle for a few seconds to clear.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Stain Block
October 2026, Version 01.01
020514050000265638

SikaStainBlock-en-GB-(10-2026)-1-1.pdf