

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor®-420 FR

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

Precautionary statements	:	<b>Prevention:</b>	
		P261	Avoid breathing mist or vapours.
		P273	Avoid release to the environment.
		P280	Wear protective gloves.
		<b>Response:</b>	
		P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
		P362 + P364	Take off contaminated clothing and wash it before reuse.
		<b>Disposal:</b>	
		P501	Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine))  
Isophorondiisocyanate homopolymer  
Hardener MI (Isophoronedim(morpholinoaldimine))  
Pentamethyl piperidylsebacate  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
4-morpholinecarbaldehyde

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hardener MTJ (Polyoxypropylene-tri(morpholinoaldimine))	1379822-00-0 700-879-7 UK-01-9733181806-8-0001	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 5 - < 10
Isophorondiisocyanate homopolymer Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 931-312-3 500-125-5 01-2119488734-24-XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 5 - < 10
Hardener MI (Isophoronedimorpholinoaldimine) Contains: 2,2-Dimethyl-3-(4-morpholinyl)propanal <= 7 %	1217271-02-7 700-584-3 UK-01-8398764756-3-0001	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 2,5
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 1

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411  specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %  Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 0,031 mg/l	>= 0,25 - < 0,5
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12-XXXX	Skin Sens. 1; H317	< 1
salicylic acid	69-72-7 200-712-3 01-2119486984-17-XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d  Acute toxicity estimate  Acute oral toxicity: 891 mg/kg	< 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects  
  
May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

areas and containers place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
		TWA	50 ppm 274 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 548 mg/m <sup>3</sup>	GB EH40
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m <sup>3</sup> (NCO)	GB EH40
		Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have		

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

	<p>become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitizer will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitizers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		STEL	0,07 mg/m <sup>3</sup> (NCO)	GB EH40

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

Colour : various

Odour : mild

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 61 °C  
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture reacts with water

### Viscosity

Viscosity, dynamic : ca. 5.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 22 hPa

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

Density : ca. 1,32 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

#### Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

#### Hardener MI (Isophoronedim(morpholinoaldimine)):

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### **reaction mass of ethylbenzene and xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

### **salicylic acid:**

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Hardener MI (Isophoronedimethyl(morpholinoaldimine)):**

Method : Regulation (EC) No. 440/2008, Annex, B.46  
Result : Skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

### Components:

#### **Hardener MI (Isophoronedimethyl(morpholinoaldimine)):**

Method : OECD Test Guideline 405  
Result : Eye irritation

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **Hardener MI (Isophoronedimethyl(morpholinoaldimine)):**

Method : Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)  
Result : May cause sensitisation by skin contact.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 45,1 mg/l  
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 12,5 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,56 mg/l  
Exposure time: 72 h

##### **Hardener MI (Isophoronedimorpholinoaldimine):**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 40,2 mg/l  
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 17,1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 89 mg/l  
Exposure time: 72 h

##### **reaction mass of ethylbenzene and xylene:**

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia (water flea)

##### **Pentamethyl piperidylsebacate:**

Toxicity to fish : LC50 (Fish): 0,97 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

- European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

- ADR : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

- ADR : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.4 Packing group

- ADR : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA (Cargo) : Not regulated as a dangerous good
- IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 11,5% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 11,5% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

#### Other regulations:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361d	:	Suspected of damaging the unborn child.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikafloor®-420 FR

Date of last issue: 21.06.2023  
Revision Date: 27.11.2023

Version 6.6

Print Date 29.02.2024

GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN