

## PRODUCT DATA SHEET

# Sikagard® Patio Gloss

Wet look patio and driveway sealer and protector.

### PRODUCT DESCRIPTION

Sikagard® Patio Gloss protects and seals patios, paths, concrete and block paving against the effects of water, weathering, petrol and green growth. Once applied, this product dries to a clear, hard-wearing, water-repelling finish that provides long-lasting protection against the elements, spillages, water penetration, mould and general wear to keep your surfaces looking new.

### USES

- Paths.
- Patios.
- Natural stone.
- Concrete and block paving.

### CHARACTERISTICS / ADVANTAGES

- Water based formulation – non-flammable, low odour.
- Improves appearance of paths/stone. Also acts as a dustproofer and facilitates easier cleaning.
- Dramatically improves water and mark resistance
- Contains a fungicide – prevents unsightly growth in the film.
- Easily cleaned with a simple detergent wash.

### PRODUCT INFORMATION

<b>Packaging</b>	5 L jerry can.
<b>Shelf Life</b>	12 months from the date of manufacture when stored according to manufacturers instructions.
<b>Storage Conditions</b>	Store at moderate (+5 to +35 °C) temperatures in original containers. PROTECT FROM FROST.
<b>Appearance / Colour</b>	White emulsion, dries clear
<b>Density</b>	ca. 1 g/cm <sup>3</sup> (20 °C)
<b>Flash Point</b>	>61 °C
<b>pH-Value</b>	8 to 9

### APPLICATION INFORMATION

<b>Yield</b>	5 L jerry will cover approximately 20 m <sup>2</sup> (based on 2 coats) surface.
<b>Ambient Air Temperature</b>	Above +5 °C

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

- Use only as directed. Store only in original container.
- Do not use on surfaces which have been treated with silicone- or stearate-based water seals.
- Do not use if rain is imminent (within 5 hours).
- Do not apply below +5 °C (air or surface temperature).
- Do not use acid-based detergents or pressure-washer to clean.
- Dispose of this product and packaging correctly. Do not allow to enter watercourses. It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Surfaces must be free from grease, dust, loose material, algae etc. Clean surfaces with SIKA® MOULDBUSTER. For bad oil stains, use a proprietary detergent and hot water. For very badly soiled surfaces, use SIKA® BRICK AND PATIO CLEANER. In all cases, wash down the cleaned surface with a hose and broom to remove all traces of cleaning product. All artificial stone (cement based) and all block pavers must be left for three months minimum after placing before overcoating with this product. This will allow salts to leach out which may otherwise cause unsightly white patches appearing beneath the sealer, especially when the patio is wet.

## APPLICATION

Stir well before use. May be applied to damp (but not wet) surfaces. Apply using a long pile roller and tray or low-pressure spray. Ensure even and thorough coverage, especially on textured finishes where ponding of the material MUST be avoided. Apply minimum of two coats, allowing 2 hours between coats. Drying time will be 4 hours from last coat at 20 °C. This will be extended at lower temperatures. Do not apply below 5 °C. Note that on textured surfaces 3 to 4 coats maybe necessary to achieve a wet look.

## CLEANING OF TOOLS

Areas treated with this product can be cleaned with warm water and detergent or SIKA® MOULDBUSTER. Do not use acid-based cleaners, as these will remove/discolour the product. Avoid using power washes.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited