

Sika® BituSeal S-115

DECLARATION OF CONFORMITY

No. 49887696

| | | |
|----|--|--|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | 49887696 |
| 2 | INTENDED USE/S | EN 13967 (type T) Prefabricated self-adhesive bituminous waterproofing sheet with HDPE film total 1.5mm thick according to EN 13967 (type T) Damp proofing and waterproofing of all kinds of below ground structures |
| 3 | MANUFACTURER: | Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 2+ |
| 6a | HARMONISED STANDARD: | EN 13967 (type T) |
| | Approved body/ies: | 0836 |

Declaration of Conformity

Sika® BituSeal S-115

49887696

2021.09 , ver. 2

1026

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Harmonised Technical Specification |
|---|------------------------|-----------|------------------------------------|
| Water tightness to liquid water | Pass | System 2+ | EN 13967 (type T) |
| Resistance to Static Load | kg ≥ 20 | System 2+ | |
| Durability of Watertightness against ageing | Pass | System 2+ | |
| Durability of Watertightness against chemicals | Pass | System 2+ | |
| Resistance to Impact | mm ≥ 500 | System 2+ | |
| Resistance to tear (Nail Shank) CD | N ≥ 100 | System 2+ | |
| Resistance to tear (Nail Shank) MD | N ≥ 100 | System 2+ | |
| Shear resistance of joints | N/50mm Long ≥ 180 | System 2+ | |
| Flexibility at low temperature | °C -23 | System 2+ | |
| Durability after artificial ageing / Watertightness | Pass | System 2+ | |
| Reaction to Fire | NPD | System 2+ | |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Steve Armfield
 Function: Product Manager
 At Sika Limited on 08 September 2021

Name : Martin Liska
 Function: R&D Manager
 At Sika Limited on 08 September 2021




End of information as required by UKCA

Declaration of Conformity

Sika® BituSeal S-115
 49887696
 2021.09 , ver. 2
 1026





21

Sika Limited, Hertfordshire, United Kingdom

DoC No. 49887696

EN 13967 (type T)

Approved Body 0836

Prefabricated self-adhesive bituminous waterproofing sheet with HDPE film total 1.5mm thick according to EN 13967 (type T)
Damp proofing and waterproofing of all kinds of below ground structures

| | | |
|---|--------|------------|
| Water tightness to liquid water | Pass | |
| Resistance to Static Load | kg | ≥ 20 |
| Durability of Watertightness against ageing | Pass | |
| Durability of Watertightness against chemicals | Pass | |
| Resistance to Impact | mm | ≥ 500 |
| Resistance to tear (Nail Shank) CD | N | ≥ 100 |
| Resistance to tear (Nail Shank) MD | N | ≥ 100 |
| Shear resistance of joints | N/50mm | Long ≥ 180 |
| Flexibility at low temperature | oC | -23 |
| Durability after artificial ageing / Watertightness | Pass | |

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Conformity

Sika® BituSeal S-115
49887696
2021.09 , ver. 2
1026

3/4

BUILDING TRUST



Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom
www.sika.co.uk

Declaration of Conformity

Sika® BituSeal S-115
49887696
2021.09 , ver. 2
1026

