

---

# Sikatec® SNW 120

---

## DECLARATION OF PERFORMANCE

### No. 75855299

---

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	75855299
2	<b>INTENDED USE/S</b>	EN 13256:2014+A:2015 Non-woven geotextile protection sheet for waterproofing
3	<b>MANUFACTURER:</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+
6a	<b>HARMONISED STANDARD:</b>	EN 13256:2014+A:2015
	Notified body/ies:	1213

#### Declaration of Performance

Sikatec® SNW 120  
75855299  
2021.09 , ver. 1  
1088

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Tensile strength - MD	70 kN/m	System 2+	EN 13256:2014+A :2015
Tensile strength – CMD	70 kN/m	System 2+	
Elongation at maximum load – MD	70%	System 2+	
Elongation at maximum load – CMD	70%	System 2+	
Static puncture resistance (CBR)	11.5 Kn	System 2+	
Dynamic perforation resistance (cone drop)	0 mm	System 2+	
Predicted minimal durability in years in natural soils with 4 < pH < 9 and soil temperatures < 25oC	≥ 100	System 2+	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Steve Armfield  
 Function: Product Manager  
 At Sika Limited on 22 September 2021

Name : Martin Liska  
 Function: R&D Manager  
 At Sika Limited on 22 September 2021




End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikatec® SNW 120  
 75855299  
 2021.09 , ver. 1  
 1088





15

Sika Services AG, Zurich, Switzerland

DoP No. 75855299

EN 13256:2014+A:2015

Notified Body 1213

Non-woven geotextile protection sheet for waterproofing

Tensile strength - MD	70 kN/m
Tensile strength – CMD	70 kN/m
Elongation at maximum load – MD	70%
Elongation at maximum load – CMD	70%
Static puncture resistance (CBR)	11.5 Kn
Dynamic perforation resistance (cone drop)	0 mm
Predicted minimal durability in years in natural soils with 4 < pH < 9 and soil temperatures < 25oC	≥ 100

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data .

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sikatec® SNW 120  
75855299  
2021.09 , ver. 1  
1088

3/4

**BUILDING TRUST**



**Sika Limited**  
Watchmead  
Welwyn Garden City  
Hertfordshire  
AL7 1BQ  
United Kingdom  
[www.sika.co.uk](http://www.sika.co.uk)

**Declaration of Performance**  
Sikatec® SNW 120  
75855299  
2021.09 , ver. 1  
1088

**4/4**

**BUILDING TRUST**

