

PRODUCT DATA SHEET

SikaWall® Deep Gap Filler

Ready mixed filler for filling deep holes in one application.

PRODUCT DESCRIPTION

SikaWall® Deep Gap Filler is a high-performance ready mixed filler, formulated with ceramic spheres, that can fill deep holes up to 50 mm in one application, with no need for secondary filling to build up or level off. SikaWall® Deep Gap Filler will not shrink, sag or crack and dries to a smooth, light grey finish, which requires little to no sanding and can be ready to paint or wallpaper in just 30 minutes. Suitable for repairs to wood, plaster, masonry, cement, stone, brick and rendering.

USES

For filling holes up to 50 mm deep in plaster, brick, stone, wood, render, cement and masonry, including on ceilings. Interior use only.

CHARACTERISTICS / ADVANTAGES

- Fills voids up to 50 mm deep in one application.
- Lightweight and easy to apply.
- Finishes to a smooth surface, no sanding required.
- No sagging.
- Non-shrink.
- Quick drying.
- Overpaintable with most solvent-based and emulsion paints.
- Overstainable.

PRODUCT INFORMATION

Packaging	1 L tub
Appearance / Colour	Light grey paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions
Storage Conditions	Store between +5 °C and +30 °C
Density	1.15 - 1.25 g/cm ³
pH-Value	8.3 - 9.9
Viscosity	60,000 to 150,000 cP @ 20°C, 50 % RH
Movement Capability	Low/ moderate

APPLICATION INFORMATION

Layer Thickness	50 mm in one coat - further layers may be built up
Ambient Air Temperature	+5 °C to +30 °C

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not use in areas subject to constant water immersion.
- Do not use externally.
- Do not use for structural repairs or to nail or screw into.
- Absorption of the filler may be different to the surrounding area. If filler shows through after painting, simply apply further coats.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry, free from dust, grease and other contamination. Any nail or screw heads should be painted with an oil-based paint.

APPLICATION

Stir SikaWall® Deep Gap Filler to a smooth paste. If product is too dry, add a few drops of water and re-stir. Apply using a flexible filler knife, smoothing down to achieve a perfect surface that will not need sanding. When filling a large surface area, it may not always be possible to achieve a completely level finish. However, SikaWall® Deep Gap Filler is easy to sand if necessary.

Deep holes up to 50 mm can be filled in one application with no need to build up in several layers.

CLEANING OF TOOLS

All tools should be cleaned immediately after use with warm, clean water. Alternatively, use Sika® Wonder Wipes.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

SikaWall® Deep Gap Filler
April 2026, Version 01.01
021840303000263308

SikaWallDeepGapFiller-en-GB-(04-2026)-1-1.pdf