According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD TECNIC FIRE SEALANT 300 INTUME

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

## 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### **Additional Labelling**

EUH208 Contains 1,2-benzisothiazol-3(2H)-one (BIT), 2-methyl-2H-isothiazol-3-one

(MIT), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-

2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Revision Date: 14.10.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 55965-84-9, 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, 2-methyl-2H-isothiazol-3-one (MIT), 2682-20-4. Please use treated articles responsibly.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Components	0.0.0.11	loi '6' '	0 , ,;
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <
(BIT)	220-120-9	Acute Tox. 2; H330	0,025
	01-2120761540-60-	Skin Irrit. 2; H315	
	XXXX	Eye Dam. 1; H318	
		Skin Sens. 1A; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 1;	
		H410	
		M-Factor (Acute	
		aquatic toxicity): 1	
		M-Factor (Chronic	
		aquatic toxicity): 1	
		specific concentration	
		limit	
		Skin Sens. 1A; H317	
		>= 0,036 %	
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		450 mg/kg	
		Acute inhalation tox-	
II		icity (dust/mist): 0,21	
		• ` '	
		mg/l	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

2-methyl-2H-isothiazol-3-one (MIT)	2682-20-4 220-239-6 01-2120764690-50- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400	>= 0,0002 - < 0,0015
		Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 200 mg/kg	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

reaction mass of 5-chloro-2-55965-84-9 Acute Tox. 3: H301 >= 0.0002 - < methyl-2H-isothiazol-3-one and 2-911-418-6 Acute Tox. 2; H330 0,0015 methyl-2H-isothiazol-3-one (3:1) 01-2120764691-48-Acute Tox. 2; H310 Skin Corr. 1C; H314 XXXX Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 **EUH071** M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % specific concentration limit Skin Irrit. 2; H315 0,06 - < 0,6 % specific concentration limit Eye Irrit. 2; H319 0,06 - < 0,6 % specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % specific concentration Eye Dam. 1; H318 >= 0,6 %

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

Substances with a workplace exposure limit :				
Titanium dioxide (> 10 μm)	13463-67-7		>= 1 - < 2,5	
	236-675-5			
	01-2119489379-17-			
	XXXX			

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

Risks : No known significant effects or hazards.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: For personal protection see section 8. Personal precautions

6.2 Environmental precautions

**Environmental precautions** No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Hygiene measures When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Advice on common storage No special restrictions on storage with other products.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

age stability

Further information on stor- : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable	10 mg/m3	GB EH40
		dust)		
		TWA (Respirable	4 mg/m3	GB EH40
		dust)	_	

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Eye/face protection Safety glasses

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Recommended: Butyl rubber/nitrile rubber gloves.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### **Environmental exposure controls**

General advice : No special environmental precautions required.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour various

Odour slight

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

Flash point 100 °C

Auto-ignition temperature No data available

Decomposition temperature No data available

8.0 - 9.0 pН

**Viscosity** 

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

Viscosity, dynamic : 250.000 mPa.s (20 °C)

Viscosity, kinematic : > 30 mm2/s (40 °C)

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 23 hPa

Density : ca. 1,61 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified due to lack of data.

### **Components:**

### 1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 450 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0,21 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LC50: 0,21 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

#### 2-methyl-2H-isothiazol-3-one (MIT):

Acute oral toxicity : LD50 (Rat): 200 mg/kg

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

#### Skin corrosion/irritation

Not classified due to lack of data.

## Serious eye damage/eye irritation

Not classified due to lack of data.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

#### Respiratory sensitisation

Not classified due to lack of data.

### **Components:**

### 1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

Not classified due to lack of data.

### STOT - repeated exposure

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

## 1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3 mg/l

aquatic invertebrates Exposure time: 48 h

M-Factor (Acute aquatic tox- : 1

icity)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

M-Factor (Chronic aquatic

toxicity)

2-methyl-2H-isothiazol-3-one (MIT):

M-Factor (Acute aquatic tox- : 10

icity)

10

M-Factor (Chronic aquatic

toxicity)

1

1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox- : 100

icity)

100

M-Factor (Chronic aquatic

toxicity)

100

100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Revision Date: 14.10.2024

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 10 waste adhesives and sealants other than those

mentioned in 08 04 09

#### **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

IMDG : Not regulated as a dangerous goodIATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the fol-

lowing entries should be considered:

Number on list 52: 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Revision Date: 14.10.2024

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

: Not applicable

Control of Major Accident Hazards Regulations Not applicable

2015 (COMAH)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eye damage. H318

Fatal if inhaled. H330

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Eve Dam. Serious eye damage Skin Corr. Skin corrosion Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

GB EH40 UK. EH40 WEL - Workplace Exposure Limits

Long-term exposure limit (8-hour TWA reference period) GB EH40 / TWA European Agreement concerning the International Carriage of ADR

Dangerous Goods by Road

CAS **Chemical Abstracts Service** DNEL Derived no-effect level

EC50 Half maximal effective concentration **GHS** 

Globally Harmonized System IATA

International Air Transport Association

**IMDG** International Maritime Code for Dangerous Goods

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL** 

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC Substances of Very High Concern

Very persistent and very bioaccumulative vPvB

#### **Further information**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



# **EVERBUILD TECNIC FIRE SEALANT 300 INTUME**

Date of last issue: 18.06.2024 Version 8.0 Print Date 28.03.2025

Revision Date: 14.10.2024

П

GB / EN