
Sikagard-5901 Eproseal

DECLARATION OF PERFORMANCE

No. 65176090

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	65176090
2	INTENDED USE/S	EN 1504-2:2004 Surface protection systems for concrete – coating (C) – ingress protection (1.3) – moisture control (2.2).
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	SYSTEM/S OF AVCP:	System 2+ System 3
5	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	1029

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Adhesive strength by pull off	$\geq 0.8 \text{ N/mm}^2$	System 2+	EN 1504-2:2004
Permeability to water vapour	Class I $s_D < 5\text{m}$	System 2+	
Capillary absorption and water permeability	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	System 2+	
Permeability to CO ₂ (4 coats)	$s_D > 50\text{m}$	System 2+	
Reaction to fire	Euroclass A1	System 3	
Dangerous substances	Conforms to 5.3	System 2+	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Name : Rob Doherty

Name : Panassakorn Jones

Function: Head Of Product
Management Engineered
Refurbishment

Function: R & D Manager
At Sika Ltd on 28 January
2026

At Sika Ltd on 28 January 2026



.....

.....

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikagard-5901 Eproseal

65176090

2026.01, ver. 1

3202



26

Sika Services AG, Zurich, Switzerland

65176090

EN 1504-2:2004

Notified Body 1029

Surface protection systems for concrete – coating (C) – ingress protection (1.3) – moisture control (2.2).

Adhesive strength by pull off	$\geq 0.8 \text{ N/mm}^2$
Permeability to water vapour	Class I $s_D < 5\text{m}$
Capillary absorption and water permeability	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$
Permeability to CO ₂ (4 coats)	$s_D > 50\text{m}$
Reaction to fire	A1
Dangerous substances	Conforms to 5.3

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikagard-5901 Eproseal

65176090

2026.01, ver. 1

3202

3/4

BUILDING TRUST



Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikagard-5901 Eproseal
65176090
2026.01, ver. 1
3202

4/4

BUILDING TRUST

