

PRODUCT DATA SHEET

Sikafloor® Pronto Filler

Filler for PMMA based products

PRODUCT DESCRIPTION

Sikafloor® Pronto Filler is an inert filler which is used to bulk out Sikafloor® PMMA flooring resins.

USES

Sikafloor® Pronto Filler may only be used by experienced professionals.

- In combination with Sikafloor® PMMA resins.
- Preventing broadcasted sand scattered onto the resin surface from sinking down to the bottom of the layer.

CHARACTERISTICS / ADVANTAGES

- Improves mechanical properties of the resin (dependent on quantity).
- Allows for viscosity adjustment of Sikafloor® PMMA resin applications.
- Economical, easy to mix and use.
- No effect on pot life or cure rate.
- Low addition rate required to change resin viscosity.
- Inert and non-reactive.

PRODUCT INFORMATION

Packaging	25 kg Refer to current price list for packaging variations.
Shelf Life	5 years from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.
Appearance / Colour	White, fine aggregate

APPLICATION INFORMATION

Mixing Ratio	Refer to the individual System Data Sheets
Consumption	Refer to the individual System Data Sheets

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Sikafloor® Pronto Filler has been tested for suitability with Sikafloor® PMMA resins. Do not replace with alternative commercial fillers as this will affect the properties of the resins.

Do not hand mix Sikafloor® Pronto Filler, mechanically mix only.

Adhesion and hardening characteristics may be affected at high addition rates.

Protect from contact with moisture. Sikafloor® Pronto Filler must be kept dry otherwise adhesion may be affected and white patches in the final finish.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

General guide

The required amount of Sikafloor® Pronto Filler is added to the Sikafloor® PMMA resin in accordance with the appropriate System Data Sheet until fully mixed without any visible lumps. Refer to the individual System Data Sheet for further information.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sikafloor® Pronto Filler
July 2022, Version 03.01
020813010010000004

SikafloorProntoFiller-en-GB-(07-2022)-3-1.pdf