

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® C-250 Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Aerosols, Category 1 | H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Respiratory sensitisation, Category 1 | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Carcinogenicity, Category 2 | H351: Suspected of causing cancer. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure if inhaled. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758






Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

| | | |
|--------------------------|---|--|
| Hazard pictograms | : |    |
| Signal word | : | Danger |
| Hazard statements | : | H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Precautionary statements | : | Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe dust or mist. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/ attention. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. |

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling

Contains fluorinated greenhouse gases. (HFC-152a)

"As from 24 August 2023 adequate training is required before industrial or professional use."

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| 1,1-difluoroethane | 75-37-6 200-866-1 01-2119474440-43-XXXX | Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 | >= 40 - < 60 |
| Diphenylmethanediisocyanate, isomeres and homologues | 9016-87-9 Not Assigned | Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 % | >= 25 - < 40 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

| | | | |
|----------------------------------|---|--------------------|--------------|
| 2,2'-dimorpholinyl diethyl ether | 6425-39-4 229-194-7 01-2119969278-20-XXXX | Eye Irrit. 2; H319 | >= 1 - < 2,5 |
|----------------------------------|---|--------------------|--------------|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Cleaning with aprotic polar solvents must be avoided.
Consult most current local Product Data Sheet prior to any use.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|--|-----------|-------------------------------|------------------------------|---------|
| Diphenylmethanediisocyanate, isomeres and homologues | 9016-87-9 | TWA | 0,02 mg/m ³ (NCO) | GB EH40 |
| Further information: Capable of causing occupational asthma. | | | | |
| | | STEL | 0,07 mg/m ³ (NCO) | GB EH40 |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|--|-----------|---|--------------------------------------|-------------|
| Diphenylmethanediisocyanate, isomeres and homologues | 9016-87-9 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

ing limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation, especially in confined areas.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol
Colour : amber
Odour : characteristic

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 20,2 %(V)

Lower explosion limit / Lower flammability limit : 4 %(V)

Flash point : ca. -41 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture reacts with water

Viscosity

Viscosity, dynamic : 1.300 mPa.s

Viscosity, kinematic : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

Solubility(ies)

| | | |
|--|---|-----------------------|
| Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | No data available |
| Vapour pressure | : | 0,01 hPa |
| Density | : | 1,1 g/cm ³ |
| Relative vapour density | : | No data available |
| Particle characteristics | : | No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

- Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg
- Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

- Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

mation

Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

Components:

1,1-difluoroethane:

100-year global warming potential: 124

Further information: ANNEX I FLUORINATED GREENHOUSE GASES REFERRED TO IN POINT 1 OF ARTICLE 2 ; Section 1: Hydrofluorocarbons (HFCs)

The Fifth Assessment Report of the United Nations Intergovernmental Panel on Climate Change (IPCC)

Components:

1,1-difluoroethane:

20-year global warming potential: 591

100-year global warming potential: 164

500-year global warming potential: 46,8

Atmospheric lifetime: 1,6 yr

Radiative efficiency: 0,102 Wm²ppb

Further information: Hydrofluorocarbons

UNEP - Handbook for the Montreal Protocol on Substances that Deplete the Ozone Layer

Components:

1,1-difluoroethane:

100-year global warming potential: 124

Further information: Annex F - Group I: HFCs

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product :
- The generation of waste should be avoided or minimized wherever possible.
 - Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 - Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 - Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 - Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3501
IMDG : UN 3501
IATA (Cargo) : UN 3501
IATA (Passenger) : UN 3501
Not permitted for transport

14.2 UN proper shipping name

ADR : CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.
(1,1-difluoroethane)
IMDG : CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.
(1,1-difluoroethane)
IATA (Cargo) : Chemical under pressure, flammable, n.o.s.
(1,1-difluoroethane)
IATA (Passenger) : CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.
Not permitted for transport

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-------------------------|-------------------------------|------------------|
| ADR | : 2 | 2.1 |
| IMDG | : 2.1 | |
| IATA (Cargo) | : 2.1 | |
| IATA (Passenger) | : Not permitted for transport | |

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 8F
Hazard Identification Number : 23
Labels : 2.1
Tunnel restriction code : (B/D)

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 218
Packing group : Not assigned by regulation
Labels : Flammable Gas

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| | | |
|------|---|---|
| H220 | : | Extremely flammable gas. |
| H280 | : | Contains gas under pressure; may explode if heated. |
| H315 | : | Causes skin irritation. |
| H317 | : | May cause an allergic skin reaction. |
| H319 | : | Causes serious eye irritation. |
| H332 | : | Harmful if inhaled. |
| H334 | : | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | : | May cause respiratory irritation. |
| H351 | : | Suspected of causing cancer. |
| H373 | : | May cause damage to organs through prolonged or repeated exposure if inhaled. |

Full text of other abbreviations

| | | |
|----------------|---|---|
| Acute Tox. | : | Acute toxicity |
| Carc. | : | Carcinogenicity |
| Eye Irrit. | : | Eye irritation |
| Flam. Gas | : | Flammable gases |
| Press. Gas | : | Gases under pressure |
| Resp. Sens. | : | Respiratory sensitisation |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitisation |
| STOT RE | : | Specific target organ toxicity - repeated exposure |
| STOT SE | : | Specific target organ toxicity - single exposure |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 BAT | : | UK. Biological monitoring guidance values |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period) |
| ADR | : | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | : | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| IATA | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® C-250 Spray

Date of last issue: 29.09.2022
Revision Date: 28.03.2023

Version 7.2

Print Date 28.03.2023

| | | |
|--------|---|--|
| LC50 | : | test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |

Further information

Classification of the mixture:

| | |
|---------------|------------|
| Aerosol 1 | H222, H229 |
| Acute Tox. 4 | H332 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Resp. Sens. 1 | H334 |
| Skin Sens. 1 | H317 |
| Carc. 2 | H351 |
| STOT SE 3 | H335 |
| STOT RE 2 | H373 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

GB / EN