

# Sika MaxMix® POWDER MORTAR TONE-BUFF

## **DECLARATION OF PERFORMANCE**

# No. 90744029

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	90744029
2	INTENDED USE/S	Powder mortar tone for use in concrete, mortar and grout applications
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	N/A
5	SYSTEM/S OF AVCP:	2+
6a	DESIGNATED STANDARD:	BS EN12878:2014
	Conformity Assessment body/ies:	0086

Sika MaxMix® POWDER MORTAR TONE 90744029 2025/07, ver. 01 1213

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Setting Time	Pass		
Water Soluble Content	Category A		
Soluble Chloride	Category A		
Total Chlorine	Category A		
Loss on Ignition @ 1000°C	14 %		BS EN12878: —— 2014
Dangerous substances	None		2014

## 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas Function: Technical Product

Coordinator

At Leeds on 30 July 2025

Name: Charlotte Ogden Function: Product Manager At Leeds on 30 July 2025

Coolen

End of information as required by UKCA





ter Soluble Content  Luble Chloride  Category A  Category A  Category A  Category A  S on Ignition @ 1000°C  14 %		ding Products LTD, Leeds, UK DP No. 90744029
Powder mortar tone for use in concrete, mortar and grout application  ting Time ter Soluble Content Category A  uble Chloride al Chlorine Son Ignition @ 1000°C  14 %	В	S EN12878:2014
ting Time Pass ter Soluble Content Category A  uble Chloride Category A  al Chlorine Son Ignition @ 1000°C  14 %	Conformit	y Assessment Body 0086
ter Soluble Content  Luble Chloride  Category A  Category A  Category A  Category A  S on Ignition @ 1000°C  14 %	Powder mortar tone for use i	n concrete, mortar and grout applications
ter Soluble Content  Luble Chloride  Category A  Category A  Category A  Category A  S on Ignition @ 1000°C  14 %		
uble Chloride Category A al Chlorine Category A s on Ignition @ 1000°C 14 %	Setting Time	Pass
al Chlorine Category A s on Ignition @ 1000°C 14 %	Water Soluble Content	Category A
s on Ignition @ 1000°C 14 %	Soluble Chloride	Category A
<del></del>	otal Chlorine	Category A
	oss on Ignition @ 1000°C	14 %
ngerous substances None	Dangerous substances	None
ngerous substances None	ss on Ignition @ 1000°C	14 %

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

#### **LEGAL NOTE**

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

**Declaration of Performance** Sika MaxMix® POWDER MORTAR TONE 2025/07, ver. 01



1213

90744029